

## AEGDL16021/ AEGDL16022: AEG 15W LED Recessed Downlight

**LED Source** 

1800 lm

Voltage

AC 100-277V

**Power** 

15W

Lifespan

50,000 hr

Warranty

3 Years



- AEGDL16021/22 is a professional recessed downlight that uses COB LED technology, allowing high luminous efficacy
- It is characterized by excellent thermal management due to its die casting aluminum heat sink.
- It is suitable for areas requiring high light output and heavy use, 24/7 operation, such as: hospitals, hotels and airports.

Model Number: AEGDL16021/ AEGDL16022

#### **Features:**

- Bridgelux COB technology
- Non-Flickering
- Meanwell Driver
- Glass: Clear / Frosted
- IP: 20
- Lifespan: 50,000 hr
- Warranty: 3 Years based on 24/7 use
- Standards: CE, RoHS

#### **Light Characteristics:**

- LED Source: 1,800 lm

- Lumen Efficacy: 120 lm/W

- Beam Angle: 65°

- CRI: >80

- Color Temperature:

Warm (3000K)

Neutral (4000K)

Cool (5000K)

#### **Electrical Characteristics:**

- Power: 15W

- Voltage: AC 100-277V

- Frequency: 50/60 Hz


- PF: >0.9

#### **Heat Management:**

- Excellent Heat Management
- Aluminum Die Casting Heat Sink
- Operating Temperature:  $-10^{\circ}\text{C} \rightarrow 35^{\circ}\text{C}$

# **AEG**

## **Dimensional Drawing:**



#### **Product Dimensions:**

Diameter: 240 mmCut-off: 220 mmHeight: 155 mm

### **Package Dimensions:**

Interior box size: 260x260x170 mmOuter CTN size: 540x540x355 mm

- QTY per CTN: 8 pcs

Notes .....

- The working voltage for the product is 100-277V. Please make sure that the working voltage is 100-277V before you connect it to the power supply.
- Please check whether there is any damage caused by delivery before you use the products. If there is any flaw, please do not use and inform the supplier.
- Suitable for indoor use only.